


				PAR 30 HIT-TC-CE / G8,5 OSRAM: HCI-TC PHILIPS: CDM-TC	2100 MEDIO DRIVE OVER
<ul style="list-style-type: none"> • Body from aluminium alloy. • Locking ring (flange) from aluminium alloy. • 12mm clear flat tempered glass cover. 					
				PRICE LIST	
CODE	DESCRIPTION	T	COLOUR	Integrated Control Gear	
842155	80 30 033 2x15° 1x max.75W PAR30 / E27 152°C		Black		
842165	80 30 040 2x3° 1x20W HIT-TC-CE / G8.5 55°C		Black		
842175	80 30 041 2x6° 1x20W HIT-TC-CE / G8.5 55°C		Black		
804203	Outercasing 89 45 030				

T Glass surface temperature.

Roll over weight 4.000kg.




For the proper installation of the fitting an effective drainage as well as a 20-30 cm deep layer of gravel must be intended for dewatering.

Fittings come with 3x1.5mm² or 3x2.5mm² H07RNF cables, 1m length.

				OSRAM: HALOSPOT 111 PHILIPS: ALULINE 111 OSRAM: DULUX T / E PHILIPS: PL-T / 4P OSRAM: HQI-TS, HCI-TS PHILIPS: MHN-TD, CDM-TD	OSRAM: DULUX D PHILIPS: PL-C OSRAM: HCI-T PHILIPS: CDM-T OSRAM: NAV-TS PHILIPS: -	2100 MEDIO DRIVE OVER
<ul style="list-style-type: none"> • Body from aluminium alloy. • Locking ring (flange) from aluminium alloy. • 12mm clear flat tempered glass cover. 						
				PRICE LIST		
CODE	DESCRIPTION	T	COLOUR	Integrated Control Gear		
842195	80 30 096 2x25° 1x18W TC-D / G24d-2 42°C		Black			
842205	80 30 162 2x51,8° 1x26 or 32W TC-TEL / GX24q-3 50°C		Black			
842215	80 30 080 2x3° 1x35W HIT-CE / G12 60°C		Black			
842225	80 30 081 2x6° 1x35W HIT-CE / G12 60°C		Black			
842325	80 30 083 2x34° 1x35W HIT-CE / G12 60°C		Black			
842335	80 30 085 asym.16° 1x35W HIT-CE / G12 60°C		Black			
842235	80 30 110 2x3° 1x70W HIT-CE / G12 133°C		Black			
842245	80 30 111 2x6° 1x70W HIT-CE / G12 108°C		Black			
842485	80 30 113 2x34° 1x70W HIT-CE / G12 98°C		Black			
842495	80 30 115 asym.16° 1x70W HIT-CE / G12 89°C		Black			
842255	80 30 134 2x16,4° 1x70W HIT-DE or HST-DE / RX7s 105°C		Black			
804204	Outercasing 89 45 031					

T Glass surface temperature.

Roll over weight 4.000kg.



For the proper installation of the fitting an effective drainage as well as a 20-30 cm deep layer of gravel must be intended for dewatering.

Fittings come with H07RNF cables, 1m length.