

**BEAM7 LED IP65**


Surface wall mounted luminaire with power LED chip. It is ideal for a wide range of outdoor applications due to its high protection degree IP65. Available with one or two-way light distribution and with different beam angles.

**Technical Features**

- Aluminium body, painted electrostatically in selected colour.
- Mounting base from die-cast aluminium.
- Tempered protection glass.
- Beam distribution lens.
- Silicone sealant.
- Pure light without IR/UV radiation.
- From 3W with 300 Lumen up to 12W 900 Lumen.
- Operation life: 50,000 hours with efficiency > 70% of the initial luminous flux.

**Upon request:**

Available with highest colour rendering index (CRI)



To ensure the degree of protection (sealing), the use of flexible power supply cable type H07RN-F is required.

BEAM 7 LED IP65


BEAM 7 - ONE WAY



CE	F	850°C	IP 65
LED	350/500mA	ta 25°C	

- Beams: Spot, Medium, Wide.  
 - 1x1W power consumption driven at 350mA.  
 - 1x2W power consumption driven at 500mA.  
 - Efficiency:  
 1x1W: 4000 K: 321 Lumen, CRI: min. 75  
 1x1W: 3000 K: 300 Lumen, CRI: min. 80  
 1x2W: 4000 K: 450 Lumen, CRI: min. 75  
 1x2W: 3000 K: 420 Lumen, CRI: min. 80  
 Maximum: 107 Lm/W

Code	Description	Kg
85770	BEAM7 ONE WAY 1 LED x 1W (Integrated Control Gear)	0,500
85771	BEAM7 ONE WAY 1 LED x 2W (Integrated Control Gear)	0,500




BEAM 7 - TWO WAY



CE	F	850°C	IP 65
LED	350/500mA	ta 25°C	

- Beams: Spot, Medium, Wide.  
 - 2x1W power consumption driven at 350mA.  
 - 2x2W power consumption driven at 500mA.  
 - Efficiency:  
 1+1x1W: 4000 K: 107+107 Lumen, CRI: min. 75  
 1+1x1W: 3000 K: 100+100 Lumen, CRI: min. 80  
 1+1x2W: 4000 K: 150+150 Lumen, CRI: min. 75  
 1+1x2W: 3000 K: 140+140 Lumen, CRI: min. 80  
 Maximum: 107 Lm/W

Code	Description	Kg
85776	BEAM7 TWO WAY 1+1 LED x 1W (Integrated Control Gear)	0,650
85777	BEAM7 TWO WAY 1+1 LED x 2W (Integrated Control Gear)	0,650



LED COLOUR CODES:

2 Warm 3 Neutral


Beams Codes:

10 spot/spot 30 medium/medium 45 wide/wide 90 spot/medium 91 spot/wide 92 medium/wide


Colour Codes:

0 Colours 1 White 2 Titan 3 Black 4 Chrome 5 matt Alum.

Versions



BEAM 7 - ONE WAY  
 1/2W  
 OPTICS  
 S / M / W



BEAM 7 - TWO WAY  
 1+1/2+2W  
 OPTICS  
 S / M / W