

SLIM 3 - LED



A linear LED luminaire which illuminates facades uniformly and emphasises their surfaces. Although buildings fade over time, the proper lighting can add value to them, highlight their uniqueness and make a lasting impression.

Technical Features

- Aluminium body.
- Beam distribution lens.
- Transparent PMMA profile cover.
- Silicone sealant.
- Pure light without IR/UV radiation.
- From 12W with 1285 Lumen up to 39W 4080 Lumen/m.
- Operation life: 50,000 hours with efficiency > 70% of the initial luminous flux.
- Supplied with 3x1mm NEOPRENE 1,5m cable.

Upon request:

Available with highest colour rendering index (CRI)

SLIM 3 - LED

SLIM 3 - LED




CE F 850°C IP 65

LED ta 25°C 350-1050mA

- Beams: Spot, Medium, Wide, WW.
- Aluminium body.
- PMMA cover.
- Efficiency:
- 39W: 6000 K: 4080 Lumen, CRI: min. 75
- 39W: 4000 K: 3360 Lumen, CRI: min. 75
- 39W: 3000 K: 3360 Lumen, CRI: min. 80

Code	Description	Kg
812111	SLIM 3 LED 0,53m 21W (9-21W) Adjustable (1 driver required)	1,300
812221	SLIM 3 LED 1,03m 39W (14-39W) Adjustable (1 driver required)	1,800
812331	SLIM 3 LED 1,53m 65W (20-65W) Adjustable (2 drivers required)	2,300




SLIM 3 - ACCESSORIES



Grid for accessories.

- Aluminium brackets.

Code	Description	Kg
800041	DRIVER max. 50W	0,300
801101	Set aluminium brackets 10cm	0,300
801102	Set aluminium brackets 20cm	0,400



Led Colour:

- 1 Cold 2 Warm 3 Neutral

Beams Codes:

- 1 spot 2 medium 3 wide 4 WW

Colour Codes:

- 0 Colours 4 Anodized

